

Datenblatt / Data Sheet

RGB-Kabel Rund

RGB-Cable Round



Technische Daten / technical data:

Bezeichnung / Description	Eigenschaft / Characteristic	
Artikelnummer / Item no.	66100023	66100024
Leiterwiderstand 0.34mm ² / Conductor resistance 0.34mm ²	≤ 60.00 Ω / km	
Leiterwiderstand 0.5mm ² / Conductor resistance 0.5mm ²	≤ 40.00 Ω / km	
Prüfspannung / Withstand Voltage	1.5kV	
Isolationswiderstand / Isolation Resistance	≥ 100MΩ x km	
Max. Strombelastbarkeit / Max. Ampacity (A)	4.5A	
Nennspannung / Wire Voltage	300V / 50Hz	
Kabel Typ / Cable type	Rund PVC 3x0.34mm ² - 1x0.5mm ² / Round PVC 3x0.34mm ² - 1x0.5mm ²	
Leiter 0,50 mm ² / Conductor 0,50 mm ²	E-Cu-Litze 19x0,18mm verz ; ETP1/EN13602	
Leiter / Conductor	E-Cu-Litze 19x0,15mm verz unilay;; ETP1/EN13602	
Aderisolation / Core Insulation	PVC / VDE 0207-363-3	
Aderdurchmesser / Core Diameter	1,45 ±0,10 mm	
Farbe / Color:	Weiß / White	
Kabellänge / Wire length	1m	2m
Abmessungen Ø / Dimension Ø (mm)	5,00 ±0,20 mm	

