



Ⓐ

Mechanical characteristics
cables

Mechanische Eigenschaften
Kabel

- Ⓒ G41: 0.6/2.8 AF Draka;
0.6/2.8C-HM (FR-NC) Bedea;
1855A Belden HDTV Miniature Precision Video Cable;
1855ENH Belden Digital Video Coax;
46899 Belden;
FRNC 0.6/2.8 AF (Minik.) PKI;
Image 360 Argosy; SDV Canford;
VDM230 Gepco;
VK5/0.6 FRLS 0.6/2.8 Percon

interface dimensions acc. to assembly code mating life

Steckgesicht nach Montageanleitung Steckzyklen

- Ⓑ TELASS CDF 70 Bedea IEC 61169-8
Ⓒ A0805 >500

Components
centre contact
outer contact
other metal parts
crimp ferrule
insulator

Bauteile
Innenkontakt
Außenkontakt
sonstige Metallteile
Crimprohr
Isolierung

Materials / Material
CuNi1Pb1P (C97)
CuZn39Pb3
CuZn39Pb3, CuSn0
Cu SF w
PE-LD

Ⓒ **Finish / Oberfläche**
NiP Au
Cu2Ni5
Cu2Ni5
Ni5

Electrical characteristics
impedance
return loss

Elektrische Eigenschaften
Wellenwiderstand
Rückflussdämpfung

75 Ω
typ.: 1 GHz-35 dB; 2 GHz-26 dB; 3 GHz-23 dB

Environmental
RoHS compliant

Umgebung
RoHS konform

2011/65/EU

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	gez./ drawn	Datum/ date	Name/ name	Gewicht/ weight (g)
				gepr./ appr	20.06.2013	BJ	ca./approx.
				Maßstab/ scale	Benennung/ title		
				2:1	BNC Straight Jack BNC-Kabelbuchse		
				untol. Maße/ dim. without tolerances according to	Unterl./ doc. type	Zeichnungsnr./ drawing no.	
				K	J01003A0048		 Maße/ dimensions: mm Original : DIN A4 Blatt/ sheet 1 von/ of 1
c	24867	13.06.2013	MA	Ersatz für/ replaces			
b	20849	06.05.2009	KL	Zeichnung vom 14.10.2004			
a	20563	25.02.2009	BJ				