Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPECTRUM

Supplier's address: Wojnarowscy, Gospodarcza 16 40-432 Katowice Poland

Model identifier: WOJ+14073

Type of light source:

| Lighting technology used: | LED | Non-directional or directional: | NDLS | |
|-------------------------------|-----|---------------------------------|------|--|
| Light source cap-type | E14 | | | |
| (or other electric interface) | | | | |
| Mains or non-mains: | MLS | Connected light source (CLS): | No | |
| Colour-tuneable light source: | No | Envelope: | - | |
| High luminance light source: | No | | | |
| Anti-glare shield: | No | Dimmable: | No | |
| Product parameters | | | | |

| dicating if it refers to the flux in a sphere (360°) temperature, rounded to the near- | F 2 700 |
|--|------------|
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer4Energy efficiency classUseful luminous flux (\$\$\phi\$use), in- | |
| mode (kWh/1000 h), rounded up to the nearest integerclassUseful luminous flux (φuse), in- dicating if it refers to the flux in a sphere (360°), in a wide cone400 in Sphere (360°)Correlated colour temperature, rounded to the near-2 | |
| dicating if it refers to the flux in a sphere (360°), in a wide coneSphere (360°) rounded to the near- | 2 700 |
| (120°) or in a narrow cone (90°)est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set | |
| On-mode power (Pon), ex- 4,0 Standby power (Psb), expressed in W and rounded to the second decimal 0 | 0,00 |
| Networked standby power (Pnet) for CLS, expressed in W and rounded to the second dec- imal-Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 82 |
| Outer dimen- Height 78 Spectral power dis- See | e image |
| sions without separate con- trol gear, light- ing controlWidth45tribution in the range 250 nm to 800 nm, at full-loadin la | ast page |

| parts and non- lighting con- trol parts, if any (millime- tre) | | | | | |
|--|------|--|----------------|--|--|
| Claim of equivalent power ^(a) | Yes | If yes, equivalent power (W) | 35 | | |
| | | Chromaticity coordi- nates (x and y) | 0,466 0,420 | | |
| Parameters for LED and OLED light sources: | | | | | |
| R9 colour rendering index value | 14 | Survival factor | 0,90 | | |
| the lumen maintenance factor | 0,90 | | | | |
| Parameters for LED and OLED mains light sources: | | | | | |
| displacement factor (cos φ1) | 0,96 | Colour consistency in McAdam ellipses | 5 | | |
| Claims that an LED light source replaces a fluorescent light source without integrated bal- last of a particular wattage. | _(b) | If yes then replace- ment claim (W) | - | | |
| Flicker metric (Pst LM) | 0,2 | Stroboscopic effect metric (SVM) | 0,1 | | |

(a)_{'-'} : not applicable;

(b)'_-' : not applicable;

